



AD 100 GLT Push Button



- ▶ Trigger push button in direct current technology
- ▶ For connecting to a hold-up camera, for example
- ▶ Cable can be surface- or flush-mounted

The AD 100 GLT push button is for unobtrusive manual triggering in the event of suspicious circumstances (e.g. for a hold-up camera) at work places that are in potential danger of being held up, such as banks, jewelry shops and businesses, or private households.

Certifications and Approvals

Region	Certification
Europe	CE AD 100 GLT

Parts Included

Type	Qty.	Component
AD 100 GLT	1	Push button incl. adhesive seal

Technical Specifications

Alarm contact (Changeover contact)	30 V/300 mA
Ambient temperature	0 °C to 50 °C
Ambient climates	DIN 40 040 R14
Protection type	IP 40
Environmental class	2
Housing	
• Housing material	ABS
• Housing color	RAL 9002
• Cover color	Gray
Weight	Approx. 0.07 kg
Dimensions (D x H)	81 x 31 mm

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by