

ARCW33BPH5B201A Card reader, OSDP, standard, keypad

STid Architect



The STid reader has three different form factors: it is pre-configured and programmed, ready to use and available in black color. It can be surface-mounted and an optional mounting box can be used. This reader is suitable for the US Gang Box, and it complies with the European standard as well. To provide a wide range of solutions, the reader is fully compatible with the Bosch Access management portfolio, including not only the Management Software Systems (Access Management System - AMS - and Building Integration System - BIS), the Access Modular Controller (AMC2), but also the entire MIFARE credential portfolio. The STid reader is very simple to use, and provides clear feedback to the user during operation, due to the LED and beeper. Because the reader is IP65 and IK08 rated, it is optimally suited for outdoor environments, and provides a high level of resistance against vandalism.

Installation/configuration notes

The terminal interface of the reader is so easy to install. A variety of card data formats are supported based on the card technology, including 32bit and 56bit formats. Due to the integrated audio, the cardholder can very easily distinguish between access granted and access denied.



- ▶ 13.56 MHz proximity compatible with access controllers with RS485 interface
- ▶ IP65 rated for indoor and outdoor use
- ▶ Supports MIFARE DESFire EV1 and EV3 (Bosch coded), MIFARE Classic (CSN) and MIFARE DESFire EV1, EV2 and EV3 (CSN)
- ▶ OSDP V2 Secure Channel support
- ▶ Compatible with AMS software (AMS 5.2 and above) and with the OSDP AMC2 controllers

Compatibility

The configuration card (CTN: ARA-OSDP-ARCBC) enables STid OSDP readers to read the Bosch coded MIFARE DESFire credentials. These readers can be used with AMS 5.2 and above, and with the OSDP AMC2 controllers.

Parts included

| Quantity | Component |
|----------|-------------------|
| 1 | Reader module |
| 1 | Installation note |
| 2 | Screws |
| 1 | Locking bar |
| 1 | Condenser |
| 1 | Resistor |

Technical specifications

Mechanical

| | |
|-----------------------------|------------------------------|
| Dimensions (H x W x D) (mm) | 106.64 mm x 80 mm x 25.70 mm |
| Dimensions (H x W x D) (in) | 4.21 in x 3.15 in x 1.02 in |
| Color | Black |
| Material | Plastic |
| Mounting type | Surface-mounted |

| | |
|---------------------------------|---|
| Weight (g) | 129 g |
| Weight (lb) | 0.2840 lb |
| Environmental | |
| Operating temperature (°C) | -30 °C – 70 °C |
| Operating temperature (°F) | -22 °F – 158 °F |
| Usage | Indoor; Outdoor |
| IP rating | IP65 |
| Impact protection | IK08 |
| Electrical | |
| Operating voltage (VDC) | 7 VDC – 28 VDC |
| Operation | |
| Audible indication | Yes |
| Credential type | Cards/keyfobs/tokens; PIN |
| Keypad | Yes |
| Optical indication | LED |
| Software compatibility | Building Integration System; Access Management System |
| Wireless transmission frequency | 13.56 MHz |
| Reading format | ISO14443A CSN 32 bit; ISO14443A CSN 56 bit; MIFARE DESFire EV2; MIFARE DESFire EV1; MIFARE Classic; MIFARE DESFire EV3 |
| Read range (cm) | 0 cm – 6 cm |
| Read range (in) | 0 in – 2.36 in |
| Connectivity | |
| Reader interfaces | RS485 |
| System integration | |
| Protocols / standards | OSDP |

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Platz 1
D-70839 Gerlingen
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Ordering information**ARCW33BPH5B201A Card reader, OSDP, standard, keypad**

Standard OSDP reader with keypad for MIFARE Classic, MIFARE EV1, EV2 and EV3, black, IP65 rated for indoor and outdoor.

Order number **ARCW33BPH5B201A | F.01U.410.591**

Accessories**ARA-OSDP-ARCBC Configuration card set, OSDP, BC, ARC**

Set of 8 configuration cards for STid OSDP readers that allow to read Bosch-coded MIFARE DESFire credentials.

Order number **ARA-OSDP-ARCBC | F.01U.419.779**

KITBCBOSCH20 Address config card set for ARC OSDP

Set of eight cards for the configuration of the reader address 1 to 8.

Order number **KITBCBOSCH20 | F.01U.412.888**

KIT-SPACER-ARC-NO Wallmount box, ARC, black, 5pcs

Wallmount box for the standard STid readers with and without keypad, black.

Order number **KIT-SPACER-ARC-NO | F.01U.410.592**