

Control Panels

B Series

G Series

Commercial Type Number

B5512

B6512

B8512G

B9512G









| | | Control and Control and Control and Control | | | |
|------------------------|------------------------------------|--|--|--|--|
| Integration | | IP Video, BIS, BVMS | IP Video, Access Control, BIS, BVMS | IP Video, Access Control, BIS, BVMS | IP Video, Access Control, BIS, BVMS |
| Advanced Features | Area arming | Interior + Perimeter | Interior + Perimeter | Interior + Perimeter | Interior + Perimeter |
| | Link multiple areas | • | • | • | • |
| | Area re-arm | • | • | | |
| | Monitor delay | • | | • | • |
| | Dual authentication | • | • | | |
| | Early ambush | | • | • | • |
| | Two-man rule | | • | | |
| Communication | Options | IP*, Cellular, PSTN | IP*, Cellular, PSTN | IP*, Cellular, PSTN | IP*, Cellular, PSTN |
| | Formats | Contact ID, Modem4, Conettix | Contact ID, Modem4, Conettix | Contact ID, Modem4, Conettix | Contact ID, Modem4 Conettix |
| P | On-board Ports | Ethernet, USB | Ethernet, USB | Ethernet, USB | Ethernet, USB |
| | Conettix | • | • | | |
| | DNS support | • | • | • | • |
| | IPv4/IPv6 | ■/■ | ■/■ | ■/■ | ■/■ |
| | Encryption | AES 256-bit | AES 256-bit | AES 256-bit | AES 256-bit |
| | AutoIP Configuration | • | • | | |
| | Universal Plug and Play | | • | • | • |
| Programming Methods | | RPS via IP or USB, Keypad |
| Ease of Use | Mobile app | • | • | • | |
| | Bilingual operation (languages) | English, French, Spanish, Portuguese, Italian, Polish, Greek, Hungarian, Chinese |
| | Custom keypad text | • | • | • | |
| | Situation-sensitive on-screen help | • | | • | • |
| | Simplified menus | • | • | • | |
| Notifications | | Email, SMS text | Email, SMS text | Email, SMS text | Email, SMS text |
| Passcode Security | Authority levels | 14 | 14 | 14 | 14 |
| | User names | 32 characters | 32 characters | 32 characters | 32 characters |
| Wireless Compatibility | | RADION | RADION | RADION | RADION |
| Capacity | Areas | 4 | 6 | 8 | 32 |
| | Custom functions | 4 | 6 | 8 | 32 |
| | Doors | - | 4 | 8 | 32 |
| | IP Cameras | 4 | 6 | 8 | 16 |
| | Log events | 1024 | 1024 | 2,048 | 10,192 |
| | Outputs (onboard/expanded) | 3/40 | 3/88 | 3/96 | 3/596 |
| | Point profiles | 20 | 20 | 31 | 64 |
| | Points (total/wired/wireless) | 48/40/40 | 96/84/88 | 99/88/91 | 599/512/504 |
| | Schedules (SKEDS) | 5 | 10 | 40 | 80 |
| | Supervised keypads | 8 | 12 | 16 | 32 |
| | Users | 50 + Service | 100 + Service | 500 + Service | 2000 + Service |
| Certifications | | UL, CSFM, ULC, CE, CCC | UL, CSFM, ULC, CE, CCC | UL, ULC, CSFM, CE, CCC | UL, ULC, CSFM, CE, CCC |
| | | | | | |

[■] Available — Not available

^{*} On-board

Keypads

| | | Intrusion Applications | | | | Fire Applications | |
|------------------------------|-------------------|---|--|--|--|--|---|
| Туре | | Text | Text w/ function keys | Touch screen | Touch screen | Combination Intrusion + Fire | Fire |
| Commercial type number (CTN) | | B915 / B915i | B920 | B942B | B942W | B925F | B926F |
| | | O mines | | O SPICION CONTROL WAY Francis | () BOOKS BALL OF STATE OF STA | 0 0 0 0 0 0 0 0 0 0 | # 0 DESCONDENS |
| Function keys | Intrusion | - | | - | - | | - |
| | Fire | - | - | - | - | | |
| Display | Туре | 2-line, 18 characters | 2-line, 32 characters | Text + Icons | Text + Icons | 2-line, 32 characters | 2-line, 32 characters |
| | Bilingual support | | | | | | |
| | Languages | English, French, Spanish, Portuguese, Italian, Polish, Greek, Hungarian, Chinese | English, French, Spanish, Portuguese, Italian, Hungarian | English, French, Spanish, Portuguese, Italian, Polish, Greek, Hungarian, Chinese | English, French, Spanish, Portuguese, Italian, Polish, Greek, Hungarian, Chinese | English, French, Spanish, Portuguese, Italian, Hungarian | English, French, Spanish, Portuguese Italian, Hungarian |
| On-screen help | | - | | | | - | - |
| Indicators | All on | | • | • | • | • | • |
| | Part on | • | • | • | • | • | - |
| | Ready | | • | • | • | • | • |
| | Trouble | • | • | • | • | • | • |
| | Power | • | • | • | • | • | • |
| | Gas alarm | • | • | • | • | • | |
| | Fire alarm | - | - | - | - | • | • |
| | Silenced alarm | - | - | - | - | | |
| | Supervision error | - | - | - | - | • | • |
| Proximity reader | Audible tones | | | • | • | | |
| | Proximity reader | - | - | • | • | - | - |
| | Inputs/outputs | -/- | -/- | 4/1 | 4/1 | -/- | -/- |
| Specifications | Dimensions | 5.5" x 4.7" x 1" (139 x 118 x 23 mm) | 6.2" x 4.7" x 1" (158 x 120 x 26 mm) | 6.2" x 4.7" x 0.65" (158 x 120 x 16.5 mm) | 6.2" x 4.7" x 0.65" (158 x 120 x 16.5 mm) | 6.2" x 4.7" x 1" (158 x 120 x 26 mm) | 6.2" x 4.7" x 1" (158 x 120 x 26 mm) |
| | Connection type | SDI2 bus | SDI2 bus | SDI2 bus | SDI2 bus | SDI2 bus | SDI2 bus |

Communication modules

| Material description | | PTSN (Single phone line) | Two-way cellular* | Two-way cellular* | Remote cellular interface | Ethernet (Two-way IP) |
|------------------------------|-------------------------------|--|-----------------------------|---|--|---------------------------------|
| Commercial type number (CTN) | | B430 | B442 G Series | B443 | B450 | B426 |
| | | | | | ⊕ BOSCU | |
| IP | Supported protocols | - | Conettix | Conettix, Modem 4 | Conettix | Conettix |
| | Encryption | - | AES 256-bit | AES 256-bit | AES 256-bit | AES 256-bit |
| Display | Anti-replay/anti-substitution | - | | | | • |
| | Resistance to DoS attacks | - | | | | |
| Cellular | Communication | - | GPRS | 3G/4G GPRS, EDGE, UMTS, HSPA+ | - | - |
| | Network | - | Verizon | - | - | - |
| Connection type | Panel | Plug-in | Plug-in | Plug-in | SDI or SDI2 | SDI or SDI2 |
| | Communication path | RJ-45 | Omni-directional antenna | Omni-directional antenna | Via plug-in module | RJ-45 (Cat5 or greater) |
| Notifications | Email | - | • | - | ■** | - |
| | Text message (SMS) | - | • | • | ■ ** | - |
| | Remote Security Control app | - | • | • | ■** | • |
| Programming | Remote via RPS | | - | - | ■ ** | |
| Diagnostics | LEDs | - | • | 1 | • | • |
| | Advanced keypad diagnostics | - | • | - | • | • |
| Panel compatibility | B Series | | • | • | • | • |
| | G Series | • | • | • | • | • |
| | GV4 | - | ■ (with B450) | ■ (with B450) | • | • |
| Certifications | | UL, ULC, CSFM, FDNY-CoA, CE, ANATEL | FCC, UL, ULC, CE, ANATEL | UL, ULC, PTCRB, CE, FDNY-CoA, Rogers | NIST, FCC, UL, ULC, PTCRB, CE, ANATEL, SIA, CSFM, FDNY CoA | FCC, UL, ULC, CSFM, FDNY-CoA |

B & G Series Control Panels _ Intrusion Application

B6512/B5512/B4512/B3512



B6512/B5512



B9512G/B8512G

Keypads



B942 Touch screen



B942W Touch screen



B915/ B915iText



B920 Text w/ function keys

I/O Expansion



B208 Octoinput Module



B308 Octo-Output Module

Enclosures



B8103 Large enclosure



D8108AAttack
Resistance
Enclosure



B10 Medium enclosure

Power*



D1640

D122/

D122L

Battery

harness

Transformer

B520 AUX Power supply



D126 7Ah Battery



D135A Low-Battery Disconnect Module



DE-45-18 Transformer EU plug

*Country specific variants may appl

Residential Fire



D125BDual Class B
Initiating
Module





F220/F220-B6R Smoke Detector plus Base

Accessories



D137 Mounting bracket





D138 Mounting bracket



Mounting plate for D8103 & D8108A

Communicators



B430 Telephone (PSTN)



B450 Remote Cellular Interface



B442 Cellular GPRS



B426 Ethernet SDI or SDI2



Programming



D5500CU RPS



Installer Services Portal (available in all languages)



D5500CU-LITE RPS Lite



B99 USB Cable

Wired Sensors

Professional Series



ISC-PPR1-W16 PIR 16 x 21 m.

Ceiling Mount



DS936 Low-profile PIR 360° x 7 m.



performance PIR 360° x 21 m.

Blue Line Gen2



ISC-BPR2-W12 PIR 12 x 12 m.



ISC-BPR2-WP12 PIR, Pet Friendly 12 x 12 m.



ISC-BPQ2-W12 Quad PIR 12 x 12 m.

Request-to-exit



DS160



DS161




DS150i



DS151i

Glass Break





DS1102i



DS1103i



DS1108i

Integration

IP Video



IP camera

RADION

Wireless



RFDW-SM

Surface

Contact

B810 Wireless Receiver

RFRP

RFGB

Glass

Break

RFSM

Smoke

RFBT

Billtrap

Detector

Detector

RFDW-RM

See www.boschsecurity.com

for a complete product list.

Recessed

Contact

Wireless

Repeater



RFPR-12



Standard PIR, Pet Immune 40 x 40 ft.

RFUN

Universal

Transmitter

RFPB-SB

RFPB-TB

RFKF-TBS

RFKF-FBS Arm/Disarm Keyfobs

Panic

Buttons

Module





ARD-AYCF64



ARD-AYCE65B EM keypad,



ARD-AYZ12 EM long range

Readers



B901 Access Module

Access Control (B6512, B8512G and B9512G)



D8224

D8225

HID Prox





ARD-SER40-WI Lectus ARD-SER10-WI secure ARD-SERK40-WI iCLASS, ARD-SER90-WI Wiegand



ARD-AYH12 EM Mount RFID







ARD-AYK12 EM Mini Mullion RFID

Keypads



D8229 keypad

EM keypad



vandal-resistant



reader

Mobile Apps



Remote Security Control Mobile App





Any Bosch

Accessories

Conettix Receivers



D6100IPv6 Communications Receiver/Gateway, CPU v.61.10.00



D6600 Communications Receiver/Gateway, CPU v.01.10.00

| Notes | | |
|-------|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

A tradition of quality and innovation

For over 125 years, the Bosch name has stood for quality and reliability. Bosch is the global supplier of choice for innovative technology, backed by the highest standards for service and support. Bosch Security Systems proudly offers a wide range of security, safety, communications and sound solutions that are relied upon every day in applications around the world, from government facilities and public venues to businesses, schools and homes.

Bosch Security Systems B.V.

Torenallee 49
5617 BA Eindhoven
Phone: +31-40-2577200
For more information please visit
www.boschsecurity.com

© Bosch Security Systems 2018 Modifications reserved