

CCSE-DS Participant device short mic, black

CCS 700



The CCS700 Ultra discussion system is suitable for use in meetings and conference venues with a limited number of participants.

The CCSE-DS delegate units enable participants to actively take part in the meeting proceedings. A built-in microphone allows them to speak to the other delegates, and they can listen to the discussion using the built-in loudspeaker or (optional) personal headphones.

Functions

Microphone with flexible stem and light ring

The microphone has a flexible stem, which is easily adjustable to suit personal preferences. It also allows two people to use the same delegate unit as they can pull the microphone towards them, when it is required to speak. The microphone is fixed to the base of the delegate unit. Incorporated into the head of the microphone is a light ring which illuminates red when the microphone is on.

Built-in loudspeaker

Loudspeaker volume is set centrally at the control unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

Two headphone sockets

Two 3.5 mm (0.14 in) stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously use the unit.

- ▶ Compact, attractive design
- ▶ Built-in volume control for headphones
- ▶ Microphone with flexible stem and light ring
- ▶ Two headphone sockets

Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

Controls and Indicators

- Microphone on/off button
- Rotary volume control for adjusting headphone volume
- Loudspeaker, automatically muted when microphone is on
- Microphone 'on' indicator (red LED)
- Light ring indicator on microphone stem, lights up red when microphone is on

Interconnections

- 1 x 2 m (78.7 in) cable terminated with an 8-pin male connector loop-through connection to other delegate or chairman units
- 1 x 8-pin circular female connector for loop-through connection to other delegate or chairman units
- 2 x 3.5 mm (0.14 in) stereo headphone sockets

Installation/configuration notes

This is a professional product that should be installed, used and maintained by trained professionals only.

Parts included

Quantity	Component
1	CCSE-DS Participant device short mic, black

Technical specifications

Electrical

Nominal acoustic input at the microphone	85 dB SPL
Frequency response	200 Hz to 12.5 kHz

Mechanical

Dimensions (without microphone) (H x W x D)	54 x 136 x 138mm
Length of the microphone from the base of the stem	318 mm
Weight	1.2 kg
Mounting	Tabletop
Color	Charcoal

Environmental

Operating temperature	-5 °C to +45 °C
Storage temperature	-40 °C to +70 °C

Ordering information

CCSE-DS Participant device short mic, black

Participant device short mic, black base

Order number **CCSE-DS | F.01U.315.102**

Represented by:

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
 Bosch Sicherheitssysteme GmbH
 Robert-Bosch-Platz 1
 D-70839 Gerlingen
www.boschsecurity.com

North America:
 Bosch Security Systems, LLC
 130 Perinton Parkway
 Fairport, New York, 14450, USA
www.boschsecurity.com

Asia-Pacific:
 Robert Bosch (SEA) Pte Ltd, Security Systems
 11 Bishan Street 21
 Singapore 573943
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com