

# CSP-D00389 Mic. screw lock long stem silver

## DICENTIS



The innovative, stylish and ergonomically designed microphone with adjustable stem has a unidirectional response for optimum performance, even in noisy conditions or acoustical challenging rooms. It has low susceptibility to interference from mobile phones.

### Functions

#### Controls and indicators

- Red and green illuminator. Red indicates microphone active, green indicates request for speech accepted.

#### Interconnections

- Connector to plug and fasten the microphone.

### Parts included

Quantity	Component
1	CSP-D00389 Mic. screw lock long stem silver

### Technical specifications

#### Electrical

Power supply (VDC)	5 VDC
Power consumption (W)	0.10 W
Bandwidth (Hz)	125 Hz – 15 kHz
Dynamic range (dB)	100 dB
Nominal acoustic input level (dB SPL)	85 dB SPL

- ▶ Unidirectional microphone on adjustable stem
- ▶ Built-in plop and windshield
- ▶ Low susceptibility to mobile phones
- ▶ Screw lock robust connection

Maximum acoustic input level (dB SPL)	115 dB SPL
Self noise (dB SPL)	15 dB SPL

#### Mechanical

Microphone stem length (mm)	480 mm
Microphone stem length (in)	19.90 in
Dimensions (Ø x H) (mm) (connector)	41.3 mm x 15.9 mm
Dimensions (Ø x H) (in) (connector)	1.63 in x 0.63 in
Weight (g)	108 g
Weight (lb)	0.28 lb
Color in RAL	RAL 9022 Pearl light gray

#### Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	5 °C – 45 °C

Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

### Ordering information

#### **CSP-D00389 Mic. screw lock long stem silver**

Screw locked microphone with long stem for the DICENTIS Conference system.

Order number **CSP-D00389 | F.01U.412.152**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Tel.: +49 (0)89 6290 0  
Fax: +49 (0)89 6290 1020  
[de.securitysystems@bosch.com](mailto:de.securitysystems@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
[onlinehelp@us.bosch.com](mailto:onlinehelp@us.bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)