

# DCNM-FHH Flush hand held microphone

## DICENTIS



- ▶ Creates a floor-stand microphone position when table space is limited
- ▶ Straight 5 m cable
- ▶ Built-in plop and windshield
- ▶ Request-to-speak button and LED status indicators

The DCNM-FHH is an uni-directional, condenser microphone with built-in plop and windshield. It comfortably fits into one hand and includes a button for control.

The Flush hand held microphone is installed in participant seats without space for a tabletop or flush-mounted device. It can also create a floor-stand microphone position.

It is possible to connect the DICENTIS Flush hand held microphones to the DCNM-FAI. With two DCNM-FAI, two of these microphones can be connected to the Flush base device 2.

### Functions

- Connects to the DCNM-FAI to become part of the DICENTIS system.
- Condenser microphone with built-in plop and windshield.
- Microphone request-to-speak button.
- Red LED: Microphone on.
- Green LED: Request-to-speak confirmation.

### Parts included

Quantity	Component
1	DCNM-FHH Flush hand held microphone

### Technical specifications

#### Audio

Bandwidth (Hz)	125 Hz – 15.000 Hz
Dynamic range (dB)	100 dB

Nominal acoustic input level (dB SPL)	85 dB SPL
Maximum acoustic input level (dB SPL)	115 dB SPL
Self noise (dB SPL)	15 dB SPL

#### Mechanical

Cable length (m)	5 m
Cable length (ft)	16.4 ft
Color in RAL	RAL 9017 Traffic black

#### Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 95%

## Ordering information

### DCNM-FHH Flush hand held microphone

Flush hand held microphone with 5 m (16.4 ft) of cable length.

Order number **DCNM-FHH | F.01U.405.507**

---

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Tel.: +49 (0)89 6290 0  
Fax: +49 (0)89 6290 1020  
[de.securitysystems@bosch.com](mailto:de.securitysystems@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
[onlinehelp@us.bosch.com](mailto:onlinehelp@us.bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)