

DCNM-FIDP Flush identification panel

DICENTIS



The DCNM-FIDP supports fast participant recognition through NFC-tag identification. Identification allows for attendance registration and authorization of the participant in the meeting. After identification, the authorizations and headphone language of the participation are set for security and ease of use. The device detects ID cards between 0 and 1 cm away to prevent unintended identification.

Functions

- Supports identification cards.
- 4 Flush identification panels can be connected to a DCNM-FBD2 in dual use mode.

Interconnections

- Control interface, through RJ12, to the DCNM-FBD2 and other devices.

Parts included

Quantity	Component
1	DCNM-FIDP Flush identification panel
1	30 cm cable

Technical specifications

Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
---------------	---

- ▶ Also available in customized colors, wood, stone or metal designs
- ▶ Near-field communication card reader to identify participant
- ▶ Lighted icon guides the user
- ▶ Optional card holder
- ▶ Icon on only when the functionality is available to prevent distractions

Dimensions (H x W x D) (mm)	56 mm x 50 mm x 34 mm
Dimensions (H x W x D) (in)	2.20 in x 1.97 in x 1.34 in
Weight (g)	35 g
Weight (lb)	0.08 lb
Color (RAL)	RAL 9017 Traffic black

Electrical

Power consumption (W)	0.50 W
Operating voltage (VDC)	5 VDC

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-FIDP Flush identification panel

Flush-mounted identification panel.

Order number **DCNM-FIDP | F.01U.402.925**

Accessories

DCNM-FICH Flush ID card holder

ID card holder for the participant to automatically login when the card is parked and logout when it is removed.

Order number **DCNM-FICH | F.01U.402.928**

Software Options

DCNM-LSID License for identification at 1 seat

DICENTIS software license for enabling identification at seat in the DICENTIS Discussion device with voting, DICENTIS Discussion device with language selector, DICENTIS Discussion device with touchscreen, DICENTIS Multimedia device, and DICENTIS wireless Extended.

Order number **DCNM-LSID | F.01U.300.533**

Represented by:

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH
Robert-Bosch-Platz 1
D-70839 Gerlingen
www.boschsecurity.com

North America:

Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com