

DCNM-MICSLL Microphone screw lock long stem

DICENTIS



- ▶ Uni-directional microphone on adjustable stem
- ▶ Built-in pop and windshield
- ▶ Low susceptibility to mobile phones
- ▶ Screw lock robust connection

The innovative, stylish and ergonomically designed microphone with adjustable stem has a uni directional response for optimum performance, even in noisy conditions or acoustical challenging rooms. It has low susceptibility to interference from mobile phones.

Functions

Controls and indicators

- Red and green illuminator. Red indicates microphone active, green indicates request for speech accepted.

Interconnections

- Connector to plug and fasten the microphone.

Regulatory information

Region	Regulatory compliance/quality marks	
Europe	CE	DECL EC DCNM-MICSLL
Great Britain	UKCA	DECL UK DCNM-MICSLL

Parts included

Quantity	Component
1	DCNM-MICSLL Microphone screw lock long stem

Technical specifications

Electrical

Power supply (VDC)	5 VDC
--------------------	-------

Power consumption (W)	0.10 W
Bandwidth (Hz)	125 Hz – 15 kHz
Dynamic range (dB)	100 dB
Nominal acoustic input level (dB SPL)	85 dB SPL
Maximum acoustic input level (dB SPL)	115 dB SPL
Equivalent noise (dB SPL)	15 dB SPL

Mechanical

Microphone stem length (mm)	480 mm
Microphone stem length (in)	19.90 in
Dimensions (Ø x H) (mm) (connector)	15.90 mm x 41.30 mm
Dimensions (Ø x H) (in) (connector)	0.63 in x 1.63 in
Weight (g)	108 g
Weight (lb)	0.28 lb
Color (RAL)	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
----------------------------	--------------

Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-MICSLL Microphone screw lock long stem

Screw locked microphone with long stem for the DICIENTIS Conference system.

Order number **DCNM-MICSLL | F.01U.392.960**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Platz 1
D-70839 Gerlingen
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com