

# DCN-DVCS-CN Device with language selector and voting

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Low susceptibility to mobile phone interference
- ▶ Compact, attractive and ergonomic design
- ▶ Five voting buttons
- ▶ Built-in loudspeaker and pluggable microphone
- ▶ Channel selector with number and abbreviated channel name

The Delegate Unit with Voting and Channel Selector enables participants to speak, register a request-to-speak, listen to the speaker and vote. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The unit has five voting buttons for all types of voting. The yellow indicators above the voting buttons are used to prompt users to register their presence, to start voting and to confirm their vote. When the unit's attendance LED is yellow, it indicates the delegate is present.

The unit has a built-in channel selector, which makes it suitable for discussions in which more than one language is used and simultaneous interpretations are available. The channel selector includes up and down channel select keys and a display showing the number and the abbreviation of the languages, enabling rapid selection of the required language channel.

## Functions

- Headphone output level reduction to prevent acoustic feedback (active when listening to the floor and when the microphone is on).

- The built-in loudspeaker is muted when the microphone is on to prevent acoustic feedback
- The unit can be used as a delegate unit, as a chairman unit (DCN-DBCM chairman buttons to be ordered separately) or as a delegate unit with auxiliary button. The versatile auxiliary button can be used as an usher call, for example
- To lock the loop-through cable, a cable clamp is available (DCN-DISCLM, to be ordered separately)

## Controls and Indicators

- Five voting buttons with indicator above the buttons
- Unit activity/delegate presence indicator
- Alphanumeric display for language channel selection with number and abbreviated channel name
- Microphone button with a red, green or yellow illuminated LED. Red indicates microphone is active, green indicates request-to-speak accepted, and yellow indicates 'VIP'.
- VIP indicator is lit when the delegate is part of the notebook (only available if PC Software is used)
- Headphones volume control buttons
- Recessed 'De-init' switch

## Interconnections

- Socket for pluggable microphone

- Two 3.5 mm (0.14 in) stereo jack type headphone sockets
- 2 m (78.7 in) cable terminated within a molded six-pole circular connector
- Six-pole circular connector for loop-through connections

### Certifications and approvals

Region	Regulatory compliance/quality marks	
Europe	CE	DECL EC DCN-DVCS

### Parts included

Quantity	Component
1	DCN-DVCS-CN Device with language selector and voting

### Technical specifications

#### Electrical

Frequency response	30 Hz to 20 kHz
Headphone load impedance	> 32 Ohm < 1k Ohm
Output power	2 x 15 mW/32 Ohm

### Mechanical

Mounting	Tabletop (portable or fixed mounting)
Dimensions (H x W x D)	<b>(without microphone)</b>
Tabletop	60 x 210 x 140 mm (2.36 x 8.27 x 5.51 in)
Weight	1.15 kg (2.54 lb)
Color top	Black (RAL 9017)
Color rear	Silver (RAL 9006)

### Ordering information

#### DCN-DVCS-CN Device with language selector and voting

DCN Next Generation delegate unit with channel selector, voting, pluggable microphone, dark. Chinese version. Microphone to be ordered separately.

Order number **DCN-DVCS-CN**

#### Services

**EWE-DCNDIS-IW 12mths wrty ext DCN discussion unit**  
12 months warranty extension

Order number **EWE-DCNDIS-IW**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia