DCN-FV Flush Voting Panel

www.boschsecurity.com







- ► Stylish and modern design (IF award)
- External 'Present' contact
- ▶ LED vote confirmation indicators
- ▶ LED unit active indicator

The Flush Voting Panel allows attendance registration and six types of voting: parliamentary, audience response, multiple choice, opinion poll, rating and for/against.

The Flush Voting Panel has an external present contact, which can be used for an external present or fraud switch. Fingerprint readers are typical for the external present contact use.

The Flush Voting Panel can be click-to-fit mounted in a metal panel with a thickness of 2 mm, or can be mounted in combination with DCN-FCOUP coupling pieces and DCN-FEC end caps in any surface. The Flush Voting Panel is connected to the Dual Delegate Interface (DCN-DDI).

Functions

Controls and Indicators

Front

- Five voting buttons with yellow confirmation indicators to prompt the user to indicate presence, to vote and to confirm registration of what is voted. The buttons and indicators work as follows:
 - Yes (+), no (-) and abstain (x) (used for attendance registration, parliamentary voting and for/against)

- Numerals 1 to 5 (used for multiple choice, opinion polls and rating)
- Rating scale: -, -, 0, +, ++ (used for audience response)
- One blue LED unit active indicator to show that the system is in normal operation

Interconnections

- Two RJ11 connectors: one for connection to DCN-DDI Dual Delegate Interface, and one for loop through
- Connector for an external present contact (AMP173977-3 socket)

Technical specifications

Mechanical

Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 100 x 40.68 mm (1.57 x 3.94 x 1.68 in)
Weight	81 g (0.18 lb)
Color	

2 | DCN-FV Flush Voting Panel

DCN-FV	Silver (RAL 9022)
DCN-FV-D	Dark (graphite gray)

Ordering information

DCN-FV Flush Voting Panel

flush mounted, silver Order number DCN-FV

DCN-FV-D Flush Voting Panel Dark

flush mounted, dark Order number DCN-FV-D

Represented by:

Americas:

Bosch Security Systems, Inc. 12000 Portland Avenue South Burnsville MN 55337, USA Phone: +1-800-392-3497 Fax: +1-800-955-6831 audiosupport@us.bosch.com www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V. P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com www.boschsecurity.asia

Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.boschsecurity.com.cn

America Latina:

America Latina:
Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com