


BOSCH

Invented for life

ACD-PROX ISO Cards 50/each



- ▶ Plastic card, PVC
- ▶ Dimensions: 86 mm x 54 mm x 0.76 mm
- ▶ Imprinted card number
- ▶ Slot Punch (optional)
- ▶ PROX chip

Contactless credential with PROX chip

Functions

- PROX ISO cards have an antenna and PROX chip embedded.
- The card is recognized and read when held in front of the reader.
- The reading process is passive with a frequency of 125 kHz
- PROX cards are static credentials with a unique card number and a customer (or facility) number.

Installation/Configuration Notes

Contactless credentials with a PROX chip are ideal for installations with high-availability systems and where credentials may be exposed to abnormal conditions.

Reading ranges reach up to 12.5 cm depending on the readers used.

Technical Specifications

PROX ISO cards

| | |
|------------------------|--|
| Dimensions | 85.7 x 54 x 0.76 mm |
| Coding | Chip number, customer (or facility) code |
| Transmission frequency | 125 kHz |
| Data preservation | 10 years |
| Transaction times | < 100 ms |

Ordering Information

ACD-PROX ISO Cards 50/each

ACD-ISO CARD

Packing information: 50 cards/ each unit

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by