DCN-FMICB Flush Microphone Control Panel

www.boschsecurity.com

BOSCH
Invented for life

▶ Stylish and modern design (IF award)

▶ Microphone on/off button

▶ Colored status indicator ring

The Microphone Control Panel is connected to the Dual Delegate Interface (DCN-DDI) via one of the RJ11 control inputs.

Functions

Controls and Indicators
• One microphone control button
• Three-color illuminated ring around the microphone button which can show the following states:
  – Red - microphone is active
  – Flashing red* - last minute of speech time is active
  – Green - the delegate is listed in the request list
  – Flashing green - the delegate is the first in the request list and the next one to get the floor
  – Yellow* - the delegate is part of the Notebook and can control its microphone without interaction of the operator

* Only available with PC Control Software.

Interconnections
• 2 RJ11 connectors: one for connection to Dual Delegate Interface (DCN-DDI), and one for loop through

Technical specifications

Mechanical

Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 50 x 50 mm (1.57 x 1.97 x 1.97 in)
Weight	200 g (0.44 lb)
Color	
DCN-FMICB	Silver (RAL 9022)
DCN-FMICB-D	Dark (graphite gray)

Ordering information

DCN-FMICB Flush Microphone Control Panel
flush mounted, silver
Order number **DCN-FMICB**

DCN-FMICB-D Flush Microphone Control Panel Dark
flush mounted, dark
Order number **DCN-FMICB-D**