

CCS-Dx CCS Delegate Unit

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Unique, patent pending “Possible-To-Speak” indicator
- ▶ Compact, attractive design
- ▶ Built-in volume control for headphones
- ▶ Microphone with flexible stem and light ring
- ▶ Two headphone sockets

The CCS-Dx CCS Delegate Units enable delegates to actively take part in the proceedings. A built-in microphone allows them to speak to the other delegates, and they can listen to the discussion using the built-in loudspeaker or (optional) personal headphones.

Functions

Possible-To-Speak

A so called ‘Possible-To-Speak’ indicator is built-in showing if it is possible to switch on the microphone. This functionality is shown by a white LED combined with the ‘microphone on’ indicator.

Microphone with flexible stem and light ring

The microphone is mounted on a flexible stem, which is easily adjustable to suit personal preferences. It also allows two people to use the same delegate unit as they can pull the microphone towards them when required to speak. Incorporated into the head of the microphone is a light ring which illuminates red to indicate when the microphone is on.

Built-in loudspeaker

Loudspeaker volume is set centrally at the Control Unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

Two headphone sockets

Two 3.5 mm (0.14 in) stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously use the unit. It is also possible to connect a tape recorder to one headphone socket, and use the other headphone socket to listen to the proceedings.

Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

Compact, attractive design

Featuring modern, unobtrusive styling and finished in charcoal gray these units make a valuable addition to any venue.

Standard or Extended Length Microphone Stems

The delegate units are available with standard 313 mm (12.3 in) or extended 488 mm (19.2 in) microphone stem lengths.

Controls and Indicators

- Microphone on/off button
- Rotary volume control for adjusting headphone volume
- Loudspeaker, automatically muted when microphone is on and/or headphones are connected
- Possible-To-Speak indicator (white LED)
- Microphone 'on' indicator (red LED)
- Light ring indicator on microphone stem, lights up red when microphone is on

Interconnections

- 1 x 2 m (78.7 in) cable terminated with a 7-pole male connector for loop-through connection to other delegate or chairman units, or to a Control Unit
- 1 x 7-pole circular female connector for loop-through connection to other delegate or chairman units
- 2 x 3.5 mm (0.14 in) stereo headphone sockets

Technical specifications

Mechanical

Dimensions unit without microphone (H x W x D)	71 x 220 x 140 mm (2.8 x 8.7 x 5.5 in)	
Height with microphone in horizontal position	134 mm (5.3 in)	
Length of microphone from mounting surface	CCS-DS	CCS-DL
	313 mm (12.3 in)	488 mm (19.2 in)
Weight	approx. 1 kg (2.2 lb)	
Mounting	tabletop (portable or fixed)	
Material (top)	polymer	
Material (base)	painted metal	
Color (top)	charcoal (PH10736)	
Color (base)	charcoal (PH10736)	

Ordering information

CCS-DS CCS Delegate Unit Short Microphone

microphone stem length 313 mm (12.3 inch)

Order number **CCS-DS**

CCS-DL CCS Delegate Unit Long Microphone

microphone stem length 488 mm (19.2 inch)

Order number **CCS-DL**

DCN-DISCLM Cable Clamp (25 pcs)

25 pieces

Order number **DCN-DISCLM**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com