

# EN1249 Bill trap

www.boschsecurity.com



**BOSCH**  
Invented for life



The EN1249 Billtrap Transmitter provides the best range and reliability available today with the same profile and ruggedness as a hardwire billtrap. It can be used in any financial or retail environment.

## System overview

### Powered by Inovonics

The Inovonics EchoStream platform, powered by Inovonics wireless mesh network technology, ensures superior range, reliability, and scalability for commercial applications. Using a wide range of transmitters and repeaters, this proven technology provides flexibility and performance to meet the most stringent requirements. This exclusive protocol is available only on Inovonics EchoStream products.

### Wireless 900 MHz Band

The Inovonics EchoStream platform sends redundant information on several multi-frequency channels within the FCC Part 15 900 MHz band, providing superior range and reliability. In comparison, systems that use a single frequency technology can only send information on one narrow band channel. Any interference within the band can cause missed signals. With wireless registration, it is easy to add this technology to any application.

- ▶ Reliable communication through 900 MHz spread spectrum technology with frequency hopping
- ▶ False alarm reduction through 56 bit communication protocol and advanced signal processing
- ▶ Fully supervised with transmitter check-in once per minute
- ▶ Armed confirmation through 2 and 10 sec smart baiting LED
- ▶ Slim profile

## Functions

### Supervision

The battery activity and radio link are supervised. Monitoring helps ensure reliable operation and safeguards against undetected loss of service due to end user damage such as dropping the billtrap repeatedly, exposing it to extreme temperature, getting the billtrap wet, or other similar events.

## Certifications and approvals

Inovonics Wireless Corporation holds the following approvals:

FCC      Conforms to FCC Part 15 regulations

## Installation/configuration notes

### Compatibility Information

The EN1249 Billtrap Transmitter is compatible with the following products:

### Receivers

EN4016SK	Survey Receiver
EN4200	Serial Receiver
EN4204R	LED Receiver

**Repeater**

EN5040-T	High-power Repeater
----------	---------------------

**Parts included**

Quantity	Component
1	Billtrap
1	Battery

**Technical specifications****Electrical**

Power:	3.0 VDC, 60 mA
Battery Replacement:	Duracell DL123A, PanasonicCR123A, or approved equivalent. Not all brands are equivalent. Use the brands specified.
Battery Life (Average):	3 to 4 years. Typical battery life shown is for supervised operation.

**Mechanical**

Dimensions:	15.7 cm x 8.9 cm x 2.3 cm (6.2 in. x 3.5 in. x 0.9 in.)
-------------	--

**Environmental**

Relative Humidity:	Up to 90%, non-condensing
Temperature (Operating):	0°C to +60°C (-4°F to +140°F)

**Transmission Characteristics**

Frequency:	902 MHz to 928 MHz
------------	--------------------

**Trademarks**

Trademark names are used throughout this document. In most cases, these designations are claimed as trademarks or registered trademarks in one or more countries by their respective owners. Rather than placing a trademark symbol in every occurrence of a trademark name, Bosch Security Systems, Inc. uses the names only in an editorial fashion and to the benefit of the trademark owner with no intention of infringing the trademark.

Duracell is a registered trademark of the Gillette Company, USA, in the United States and/or other countries.

Inovonics is a trademark of Inovonics Wireless Corporation.

Panasonic is a registered trademark of Matsushita Electric Industrial Co., Ltd.

**Ordering information****EN1249 Bill trap**

Provides the range and reliability of hardwire billtraps.  
Order number **EN1249**

**Services**

**EWE-DETCR-IW 12mths wrty ext detector general**  
12 months warranty extension  
Order number **EWE-DETCR-IW**

**Represented by:**

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia