



## FAA-500-R LSN Base with Relay



FAA-500-R LSN Bases with Relay are used for installing the FAP-520 Fire Detectors in special applications, e. g. control of an emergency door in accordance with DIBt.

**Note** FAA-500 R Bases can only be used in conjunction with the 5000 Series Modular Fire Panel.

Housing color	Signal white, RAL 9003
Weight	210 g/290 g (without/with packaging)

### Ordering Information

**FAA-500-R LSN Base with Relay**  
Only used in conjunction with the 5000 Series Modular Fire Panel.

**FAA-500-R**

### Certifications and Approvals

Region	Certification
Europe	CE FAP-520 / FAA-500-R

### Technical Specifications

Connections	Power supply (0 V, + V) LSN (a-in/out, b-in, b-out) C point Shielding Relay (NO, NC, COM)
Power intake	0.2 mA
Relay contact load	1 A, 30 V DC
Cable cross section	0.3 mm <sup>2</sup> – 3.3 mm <sup>2</sup>
Dimensions	Ø 145.6 x 63.5 mm
Housing material	Polycarbonate

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6258 5511  
Fax: +65 6571 2698  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**