

## ISN-CSTB-10W Contact, 3/8", stubby, white, 10pcs



- ▶ Closed loop
- ▶ Sensitive non-stick rhodium reed
- ▶ Bent long leads keep solder off the glass of the reed
- ▶ Two solder points on the wire
- ▶ Thick plastic shell resists crushing

The magnetic contacts have a rugged, one-piece construction that eliminates the need for extra donut adapters. The compact (stubby) design allows you to use the contact in smaller spaces, without paying for a miniature design. Use in standard or tight-fitting applications.

### System overview

### Functions

### Installation/configuration notes

#### Compatibility information

The magnetic contacts are compatible with control panels that accept contact inputs.

### Parts included

Quantity	Component
10	Contact
10	Magnet

### Technical specifications

#### Electrical

Maximum operating voltage in VDC	100
Maximum conductive current in A	1

Maximum contact rating in W	10
Maximum initial contact resistance in mΩ	100
Switch configuration type	Single pole single throw (SPST)
Maximum switching voltage in VAC/VDC	110/100
Maximum switching current in A	0.5

#### Mechanical

Gap width in cm	1.5
Gap width in inch	0.6
Dimension in cm (Ø x D) (contact)	0.9 x 1.9
Dimension in inch (Ø x D) (contact)	0.35 x 0.75
Dimension in cm (Ø x D) (magnet)	0.9 x 1.9
Dimension in inch (Ø x D) (magnet)	0.35 x 0.75
Cable type	22 AWG leads standard
Cable length in cm	30.5
Cable length in inch	12
Color	White

**Environmental**

Minimum operating temperature in °C	-40
Maximum operating temperature in °C	60
Minimum operating temperature in °F	-40
Maximum operating temperature in °F	140

**Ordering information****ISN-CSTB-10W Contact, 3/8", stubby, white, 10pcs**

White recessed contact with terminal connections. 0.9 cm (0.35 in.) diameter, 1.5 cm (0.6 in) gap width.

**Package contains ten contacts and ten magnets.**

Order number **ISN-CSTB-10W | F.01U.004.792**



<https://www.boschsecurity.com>