

ISN-CSTB-TCW Contact, 3/8" quick connect, white 10pcs



The magnetic contacts have a compact, short magnet with an adhesive strip and are designed with a terminal connection for fast and easy installation. Use on window frames.

System overview

Functions

Installation/configuration notes

Compatibility information

The magnetic contacts are compatible with control panels that accept contact inputs.

Parts included

Quantity	Component
10	Contact
10	Magnet

Technical specifications

Electrical

Maximum operating voltage in VDC	100
Maximum conductive current in A	1
Maximum contact rating in W	10

- ▶ Closed loop
- ▶ Terminal connection design
- ▶ Does not require soldering or splicing
- ▶ No need to push B-Connectors (beanies) behind walls through small holes

Maximum initial contact resistance in mΩ	100
Switch configuration type	Single pole single throw (SPST)
Maximum switching voltage in VAC/VDC	110/100
Maximum switching current in A	0.5

Mechanical

Gap width in cm	1.5
Gap width in inch	0.6
Dimension in cm (Ø x D) (contact)	0.95 x 2.35
Dimension in inch (Ø x D) (contact)	0.37 x 0.92
Dimension in cm (Ø x D) (magnet)	0.95 x 1.55
Dimension in inch (Ø x D) (magnet)	0.37 x 0.61
Color	White

Environmental

Minimum operating temperature in °C	-40
Maximum operating temperature in °C	60
Minimum operating temperature in °F	-40

Maximum operating temperature in °F	140
-------------------------------------	-----

Ordering information

ISN-CSTB-TCW Contact, 3/8" quick connect, white 10pcs

White recessed contact with terminal connections. 0.95 cm (0.37 in.) diameter, 1.5 cm (0.6 in.) gap width.

Package contains ten contacts and ten magnets.

Order number **ISN-CSTB-TCW | F.01U.004.794**



<https://www.boschsecurity.com>