



Industrial sounders



The industrial sounders PA 5 and PA 10-SSM are universally applicable acoustical devices for fire alarm and security technology, IP 66, 24 VDC, EN 54-3 compliant.

Regulatory information

Region	Regulatory compliance/quality marks	
Germany	VdS	G212115 PA 5
	VdS	G212192 PA 10-SSM
Europe	CE	PA 5
	CE	PA 10-SSM
	CPD	0786-CPD-21182 PA 5
	CPD	0786-CPD-21224 PA 10-SSM
Poland	CNBOP	2848/2017 PA 10-SSM
Russia	GOST	C-DE.PB68.B.00353

Installation/configuration notes

- Use the Bosch Safety Systems Designer for reliable planning.

Industrial sounder SSM, high

- Mounting options: wall, ceiling
- Wall mounting depending on background noise: 8,3 m
- Ceiling mounting depending on background noise: 23,2 m

- Certified according to EN 54-3, type B
- High efficiency and good penetration of acoustic obstacles significantly reduce the number of sounders required
- High protection class ideally for industry applications

Industrial sounder, low

- Mounting options: wall, ceiling
- Wall mounting depending on background noise: 7 m
- Ceiling mounting depending on background noise: 18,1 m

Technical specifications

Electrical

	PA 10-SSM Industrial sounder SSM, high
Current consumption (mA)	60 mA – 485 mA
Operating voltage (VDC)	18 VDC – 30 VDC
Maximum DIN tone current consumption at 24 VDC	282 mA
Inrush current reduction	SSM module

	PA 5 Industrial sounder, low
Current consumption (mA)	6 mA – 80 mA
Operating voltage (VDC)	10 VDC – 57 VDC
Maximum DIN tone current consumption at 24 VDC	38 mA

Acoustic

PA 10-SSM Industrial sounder SSM, high	
Maximum sound pressure level at a distance of 1 m (dBA)	117 dBA
Maximum DIN tone sound pressure level at a distance of 1 m (dBA)	115 dBA
Volume control	-10 dBA
Tones	80
Tone levels externally	4

PA 10-SSM Industrial sounder SSM, high	
Color	Red
Dimension (H x W x D) (mm)	170 mm x 214 mm x 156.20 mm
PA 5 Industrial sounder, low	
Material	Plastic
Color	Red
Dimension (H x W x D) (mm)	135 mm x 163.40 mm x 132 mm

PA 5 Industrial sounder, low	
Maximum sound pressure level at a distance of 1 m (dBA)	107 dBA
Maximum DIN tone sound pressure level at a distance of 1 m (dBA)	105 dBA
Volume control	-12 dBA
Tones	80
Tone levels externally	4

Environmental

PA 10-SSM Industrial sounder SSM, high	
Operating temperature (°C)	-40 °C – 55 °C
Operating relative humidity, non-condensing (%)	0% – 90%
IP rating	IP66
Impact protection (EN 50102)	IK08

PA 5 Industrial sounder, low	
Operating temperature (°C)	-40 °C – 55 °C
Operating relative humidity, non-condensing (%)	0% – 90%
IP rating	IP66
Impact protection (EN 50102)	IK08

Mechanical

PA 10-SSM Industrial sounder SSM, high	
Material	Plastic

Tone tables			
No.	Tone type	Sound pattern	Frequency/modulation
1	No tone		
2	Sawtooth, DIN tone 33404-3 Germany (emergency signal), PFEER PTAP (EN 54-3)	N	500-1200 Hz/1 s
9	Slow whoop, fire alarm, UK BS5839-1	W	800-970 Hz/1 s
11	Interrupted tone (fast)	W	800-970 Hz/20 ms
13	Interrupted tone	/ /	700-900 Hz/0,3 s on/0,6 s off
15	Slow whoop, evacuation alarm Netherlands NEN 2575 (EN 54-3)	/ /	500-1200 Hz/3,5 s on, 0,5 s off
16	Slow whoop, evacuation alarm Australia AS2220	/ /	500-1200 Hz/3,75 s on/0,25 s off
18	Slow whoop, NFPA	/ /	422-775 Hz/0,85 s on/1 s off
22	Pulsating tone, Australien alert AS1670, ISO8201	/// /	500-1200 Hz/0,5 s on/off x 3/1,5 s off
23	Siren	/ --	500-2400 Hz/3 s rising, then constant
24	Siren	/ --	300-1200 Hz/3 s rising, then constant
25	Siren	/ --	300-800 Hz/3 s rising, then constant
26	Siren, industrial alarm Germany	/ \	150-1000 Hz/10 s rising, then 40 s constant, then 10 s falling
27	Sweeping	\ \	2400-2900 Hz/0,5 s
29	Sweeping (fast)	\ \	2400-2900 Hz/10 ms
30	Sweeping	\ \	2400-2900 Hz/70 ms
31	Sweeping, France NFC48_265	\ \	1400-1600 Hz/1 s rising, 0,5 s falling
33	Sweeping (medium), UK BS5839-1	\ \	800-1000 Hz/0,5 s
34	Sweeping (fast)	\ \	800-1000 Hz/10 ms

Tone tables			
No.	Tone type	Sound pattern	Frequency/modulation
35	Sweeping (fast), UK BS5839-1	\ \	800-1000 Hz/70 ms
36	Sweeping	\ \	700-1500 Hz/1,5 s
43	Sweeping	\ \	500-1200 Hz/1,5 s
44	Sweeping, IMO 3d, Germany KTA3901 evacuation alarm	\ \	500-1200 Hz/1 s
45	Sweeping	\ \	500-1200 Hz/3 s
46	Sweeping, general alarm Finland	\ \	500-1500 Hz/7 s
52	Continuous tone	— -	2400 Hz
53	Continuous tone	— -	2000 Hz
54	Continuous tone, Finland (all-clear signal)	— -	1500 Hz
55	Continuous tone, PFEER gas alarm	— -	1200 Hz
56	Continuous tone	— -	1000 Hz
57	Continuous tone, UK BS5839-1	— -	950 Hz
59	Continuous tone	— -	880 Hz
60	Continuous tone (EN 54-3)	— -	825 Hz
61	Continuous tone	— -	800 Hz
63	Continuous tone	— -	725 Hz
65	Continuous tone, Sweden SS031711 (all-clear signal)	— -	660 Hz
66	Continuous tone	— -	554 Hz
67	Continuous tone, Germany KTA3901 (all-clear signal)	— -	500 Hz
68	Continuous tone	— -	470 Hz
69	Continuous tone	— -	440 Hz
71	Continuous tone	— -	340 Hz

Tone tables			
No.	Tone type	Sound pattern	Frequency/modulation
77	Interrupted tone	□ [.]	2200 Hz/0,5 s on/off
82	Interrupted tone, PFEER (general alarm), UK BS5839-1 (back-up alarm)	□ [.]	1000 Hz/0,5 s on/off
83	Interrupted tone, PFEER (general alarm)	□ [.]	1000 Hz/1 s on/off
88	Interrupted tone	□ [.]	950 Hz/1 s on/off
90	Interrupted tone	□ [.]	825 Hz/0,5 s on/off
91	Interrupted tone	□ [.]	800 Hz/0,25 s on/off
92	Interrupted tone	□ [.]	800 Hz/0,25 s on/1 s off
93	Interrupted tone (fast), Horn	□ [.]	800 Hz/4 ms on/off
97	Interrupted tone	□ [.]	725 Hz/0,7 s on/0,3 s off
98	Interrupted tone, Sweden SS031711 (emergency signal)	□ [.]	700 Hz/0,125 s on/off
100	Interrupted tone, industrial alarm Germany	□ [.]	680 Hz/0,875 s on/off
101	Interrupted tone, Sweden SS031711 (important message (pre-mess))	□ [.]	660 Hz/6,5 s on/13 s off
102	Interrupted tone, Sweden SS031711 (local warning)	□ [.]	660 Hz/0,5 s on/off
103	Interrupted tone, Sweden SS031711 (air raid warning)	□ [.]	660 Hz/1,8 s on/off
104	Interrupted tone, Sweden SS031711 (emergency signal) (EN 54-3)	□ [.]	660 Hz/150 ms on/off
107	Interrupted tone, Germany KTA3901 (evacuation alarm)	□ [.]	500 Hz/0,25 s on/0,75 s off
109	Interrupted tone, Australia AS2220, AS1610, AS1670	□ [.]	420 Hz/0,625 s on/off
110	Interrupted tone, (fast variable), bell	□ [.] ↔	1450 Hz/0,69 s on/off

Tone tables			
No.	Tone type	Sound pattern	Frequency/modulation
111	Interrupted tone, ISO8201 (emergency evacuation signal), USA (evacuation alarm)	□□□ [.]	470 Hz/0,5 s on/off x 3/1,5 s off
112	Interrupted tone, ISO8201 (emergency evacuation signal)	□□□ [.]	950 Hz/0,5 s on/off x 3/1,5 s off
113	Interrupted tone, ISO8201 (emergency evacuation signal), sweeping	□□□ [.]	2850 Hz/0,5 s on/off x 3/1,5 s off
115	Interrupted tone, IMO (telephone call)	□□[.]	950 Hz/2 s on/0,5 s off/0,5 s on/1 s off
116	Interrupted tone, IMO (leave ship)	□□[.]	950 Hz/1 s on/off/3 s on/1 s off
117	Interrupted tone IMO SOLAS III/50 + SOLAS III/6.4 (general alarm)	[.]	825 Hz/2,5 s on/off x 6/7 s on
122	Alternating tone	□□.	2400s-2900 Hz/0,5 s
123	Alternating tone	□□.	2400s-2900 Hz/0,25 s
124	Alternating tone, Singapore	□□.	1000-2900 Hz/0,5 s
125	Alternating tone	□□.	1200-1400 Hz/20 ms
128	Alternating tone	□□.	825-1025 Hz/0,25 s
130	Alternating tone, UK BS5839-1 (fire alarm)	□□.	800-1000 Hz/0,5 s
131	Alternating tone, UK BS5839-1 (fire alarm, railway crossing)	□□.	800-1000 Hz/0,25 s
135	Alternating tone, UK BS5839-1 (fire alarm, increased urgency - railway crossing)	□□.	800-1000 Hz/0,125 s
142	Alternating tone	□□.	500-900 Hz/0,25 s
143	Alternating tone, industrial alarm Germany	□□.	440-660 Hz/0,125 s
144	Alternating tone	□□.	440-650 Hz/1 s
146	Alternating tone, France NFS 32-001 (fire alarm) (EN 54-3)	□□.	440-554 Hz/0,1 s/0,4 s

Tone tables			
No.	Tone type	Sound pattern	Frequency/modulation
147	Alternating tone, Sweden SS031711		440-554 Hz/1 s
148	Alternating tone, Sweden SS031711		440-554 Hz/0,5 s
152	Alternating tone (two tone chime)		800-650 Hz/0,25 s on/off x 2/2 s off

Control of the tones						
DIP-Switch						External tone selection
(Setting of basic tone)						C1 C2 C1 + C2
1	2	3	4	5	6	Basic tone
						Tone number
						1 2 88 57
On						2 128 112 57
	On					2 26 100 93
On	On					2 61 131 112
		On				9 57 11 82
On	On					15 131 52 112
	On	On				16 109 52 56
On	On	On				18 111 57 68
			On			22 16 109 68
On			On			23 131 52 112
	On	On				24 131 52 131
On	On		On			25 131 52 92
		On	On			26 2 100 93
On	On	On				27 123 52 92
	On	On				29 35 52 61
On	On	On				30 27 52 77
			On			31 131 52 57
On			On			33 30 52 35
	On		On			34 35 52 93
On	On		On			35 27 52 110

Control of the tones									
DIP-Switch						External tone selection			
(Setting of basic tone)						C1	C2	C1 + C2	
1	2	3	4	5	6	Basic tone	Tone number		
						36	146	67	57
On						43	131	52	91
	On	On				45	2	57	93
On	On	On				52	15	65	82
			On	On		54	46	54	131
On			On	On		55	131	52	128
	On		On	On		56	82	35	33
On	On		On	On		59	143	59	101
		On	On	On		60	131	52	125
On		On	On	On		65	131	52	93
	On	On	On	On		66	110	52	107
On	On	On	On	On		69	131	52	110
				On	71	131	52	93	
On				On	77	61	52	122	
	On			On	82	131	52	83	
On	On			On	83	56	2	82	
		On		On	88	2	57	128	
On		On		On	90	131	52	125	
	On	On		On	91	30	52	110	
On	On	On		On	92	33	52	57	
			On	On	93	2	128	57	
On			On	On	97	2	63	93	
	On		On	On	100	131	52	125	
On	On		On	On	101	98	102	65	
		On	On	On	103	131	65	147	
On	On		On	On	104	103	65	101	
	On	On	On	On	109	16	52	22	

Control of the tones									
DIP-Switch						External tone selection			
(Setting of basic tone)						C1	C2	C1 + C2	
1	2	3	4	5	6	Basic tone	Tone number		
On	On	On	On	On	On	110	131	61	91
				On	On	112	2	57	128
On			On	On	On	113	52	123	104
	On		On	On	On	115	117	116	44
On	On		On	On	On	116	117	93	125
		On	On	On	On	117	93	116	125
On		On	On	On	On	123	27	52	77
	On	On	On	On	On	124	53	83	2
On	On	On	On	On	On	130	2	107	67
		On	On	On	On	131	2	112	57
On		On	On	On	On	135	16	56	109
	On	On	On	On	On	142	2	54	88
On	On		On	On	On	143	59	93	33
		On	On	On	On	144	110	61	2
On		On	On	On	On	146	31	67	57
	On	On	On	On	On	148	131	52	92
On	On	On	On	On	On	152	110	61	13

Ordering information

PA 10-SSM Industrial sounder SSM, high

Universally applicable acoustical signalling for fire alarm and security technology, 117 dBA, IP 66, 24 VDC, EN 54-3 compliant.

Order number **PA 10-SSM | F.01U.393.222**

PA 5 Industrial sounder, low

Universally applicable acoustical signalling for fire alarm and security technology, 107 dBA, IP 66, 24 VDC, EN 54-3 compliant.

Order number **PA 5 | F.01U.393.223**

Represented by:

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:

Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com