LBB4560/50-US Charger cabinet for 56x LBB4540

www.boschsecurity.com





- ► Can accommodate 56 pocket receivers
- ▶ Universal mains power facility allows use worldwide
- ▶ Rapid recharging: within 1 hour and 45 minutes

The charging units are used for charging and storing the INT-RXxx Pocket Receivers.

Functions

Controls and Indicators

- On/off switch
- · Charging status indication on the pocket receivers

Interconnection

- Mains input with loop-through facility; male and female Euro mains socket
- 56 charging contacts. Compatible with INT-RXxx pocket receivers

Parts included

| Quantity | Component |
|----------|--------------------------------|
| 1 | LBB 4560/50-US Charger cabinet |
| 1 | Mains cable |

Technical specifications

Electrical

|) Hz |
|----------|
| rs |
| s in the |
| |

Mechanical

| Mounting | Screws and plugs for wall mounting included |
|---------------------------|---|
| Dimensions (H x W x D) | 130 x 680 x 520 mm (5 x 27 x 20 in) |
| Weight excl. receivers | 11.2 kg (25 lb) |
| Weight incl. 56 receivers | 18.0 kg (40 lb) |
| Color | Charcoal with grey |

Ordering information

LBB4560/50-US Charger cabinet for 56x LBB4540

Integrus charging cabinet for pocket receivers, for fixed installation. US version. Order number LBB4560/50-US

Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 emea.securitysystems@bosch.com emea.boschsecurity.com Germany: Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Germany www.boschsecurity.com

North America: North America: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com

www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia