

## NPD-9501-E Midspan 95W 1 port outdoor

### High POE midspans



- ▶ Designed for outdoor installation
- ▶ Supports high-power PoE/PoH
- ▶ Lightning suppression
- ▶ Detects and protects non-standard Ethernet terminals automatically

The 95 W midspan is a high-power PoH (Power Over HDBase T) device that provides data and power between an Ethernet switch and an IP camera. In the table below, an "X" identifies which midspans can supply power to which models of cameras.


Camera models	95 W outdoor model
AUTODOME 5000i models	X
AUTODOME 7000i - outdoor models (with heater)	X
All MIC 7000i / 7100i / 9000i models without illuminator	X
All MIC 7000i / 7100i / 9000i models with illuminator	X

#### Regulatory information

Electro-magnetic Compatibility (EMC)	Complies with FCC Part 15, and CE regulations, including EN 55032 Class B (emission), EN 55024 (Immunity), and VCCI
Product Safety	Complies with UL/cUL

Regulatory Compliance	RoHS compliant, WEEE compliant, CE	
Lightning suppression	Meets GR-1089-CORE lightning suppression demands	
Surge suppression	ITU-T. K45 for outputs communication ports	
Region	Regulatory compliance/quality marks	
Europe	CE	NPD-9501-E

## Installation/configuration notes



## Parts included

Quantity	Component
1	95W outdoor midspan
1	120 -240 VAC power plug
2	Waterproof cap covers for male RJ45 port plugs
1	Quick installation guide

## Technical specifications

### Electrical

Input voltage (VAC)	100 VAC – 240 VAC ±10%, 50/60 Hz
Output voltage (VDC)	54 VDC (nominal)
Input current (A)	2.5 A (@ 100 VAC)
Maximum output power (W)	95 W
High Power Over Ethernet (High PoE) output	Pin assignment and polarity: 4 Pair power - Pairs 1/2 (-) and 3/6 (+) - Pairs 7/8 (-) and 4/5 (+)

### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Tel.: +49 (0)89 6290 0  
Fax: +49 (0)89 6290 1020  
[de.securitysystems@bosch.com](mailto:de.securitysystems@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
[onlinehelp@us.bosch.com](mailto:onlinehelp@us.bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

Surge suppression	Yes
-------------------	-----

### Environmental

Operating temperature (°C)	-40 °C – 60 °C
Operating temperature (°F)	-40 °F – 140 °F
Storage temperature (°C)	-40 °C – 85 °C
Storage temperature (°F)	-40 °F – 185 °F
Operating relative humidity, non-condensing (%)	0% – 95%
Storage relative humidity (%)	0% – 95%
IP rating	IP67
Operating altitude	Up to 2000 m (6,560 ft)

### Construction

Dimensions (H x W x D) (in)	2.83 in x 7.36 in x 10.05 in
Dimensions (H x W x D) (mm)	72 mm x 187.7 mm x 255.4 mm
Mounting type	Wall-mounted; to a pole (25 mm - 203 mm) with the Pole mount adapter accessory (sold separately)
Weight (kg)	2.20 kg
Weight (lb)	4.90 lb

## Ordering information

### NPD-9501-E Midspan 95W 1 port outdoor

95 W outdoor PoE midspan for AUTODOME and MIC cameras

Order number **NPD-9501-E** | **F.01U.365.279**

### Accessories

#### NDA-9501-PMA Pole mount adapter for NPD-9501-E

Pole mount adapter for outdoor midspan

Order number **NDA-9501-PMA** | **F.01U.374.407**