

AT	DK	HU	LV	RU
BE	EE	IE	MT	SE
BG	EL	IS	NL	SI
CH	ES	IT	NO	SK
CY	FI	LI	PL	TR
CZ	FR	LT	PT	UA
DE	HR	LU	RO	UK



10.575 to 10.6 GHz
<20 mW
CDL2-15H

AT	DK	HU	LV	RU
BE	EE	IE	MT	SE
BG	EL	IS	NL	SI
CH	ES	IT	NO	SK
CY	FI	LI	PL	TR
CZ	FR	LT	PT	UA
DE	HR	LU	RO	UK



10.51 to 10.55 GHz
<20 mW
CDL2-15G
CDL2-15G-CHI

Manufacturing dates

For product manufacturing dates, go to <http://www.boschsecurity.com/datecodes/> and refer to the serial number located on the product label.



Changes or modifications not expressly approved by Bosch Security Systems B.V. can void the user's authority to operate the equipment.

cUL / us	Perform Walk Test at least once a year. Use only a Listed Class 2 Power Limited power source. Standby power: The Listed control unit or a listed burglary power supply must provide 4 hours of standby power. Install the unit in accordance with National Electrical Code NFPA 70 and Part 1 of the Canadian Electrical code CSA C22.1.
----------	--

FCC / ISED This device complies with part 15 of the FCC Rules and Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : 1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.


Voltage (operating)	9 to 15 VDC, 9-15 Vcc de 16 mA @ 12 Vcc en veille/en alarme, source limitée en puissance, ondulation résiduelle 1 V.
Current (max)	16 mA
Alarm relay	<35 mA, 25 V
Wiring loops	Ø 1.29 mm to 0.40 mm (16 AWG to 26 AWG) (UL: 22 AWG to 16 AWG)
	-20 °C - +55 °C (-4 °F - +131 °F) EN 50130-5 Class II: -10 °C - +55 °C (+14 °F - +131 °F) UL/ C-UL: 0 °C - +49 °C (+32 °F - +120 °F)
	0- 93% Relative humidity non-condensing

Dimensions	120 mm x 70 mm x 55 mm (4.7 in x 2.75 in x 2.2 in)
Weight	116 g (4.05 oz)



Commercial Series Gen 2 Non-Anti-mask

CDL2-15G | CDL2-15H | CDL2-15G-CHI



en Quick installation guide

Bosch Security Systems B.V.

Torenallee 49
5617 BA Eindhoven
Netherlands
www.boschsecurity.com
© Bosch Security Systems B.V., 2024

Region	Agency	Certification
USA and CA	SECURITY SIGNALING UL US LISTED	cULus UL 639, ULC S306-03, Intrusion Detection Unit, Type S (CDL2-15G)
		FCC ID: T3X-CDL2, Part 15 Subpart B and C (CDL2-15G)
		ISED IC ID: 1249A-CDL2, RSS-210, (CDL2-15G)

EU		 CE - 2014/53/EU (RED), 2011/65/EU and 2015/863 (RoHS) (CDL2-15G, CDL2-15H)
	VdS	EN EN 50131-2-4 Grade 2 (CDL2-15G, CDL2-15H) EN 50130-5, Environmental Class II EN60529, EN62262: IP41 / IK04

FR	CNPP	 AFNOR-NF&A2P CDL2-15H : EN50131-2-4 Grade 2, NF324-H58 + RTC 50131-2-4 Certificate # 2820200014 NF (AFNOR) www.marque-nf.com , A2P (CNPP): www.cnpp.com Autosurveillance à l'ouverture Immunité champ magnétique. Test sans masque de vision vertical et sans immunité aux animaux
----	------	--

AUS	ACMA	RCM
BR	ANATEL	ANATEL: 03722-24-02045 Este equipamento não tem direito à proteção contra interferência prejudicial e não pode causar interferência em sistemas devidamente autorizados
BE	ANPI	INCERT B-B09-1010
SE	SBSC	CDL2-15G : No23-280, SSF 1014, utgåva 6
UK		 CDL2-15H
CN	CSP	CSP2022031901000023 (CDL2-15G-CHI)