

PLE-2MA120-US | PLE-2MA240-US

The following correction only pertains to the version from 10/2007 of the PLE-2MA120-US/PLE-2MA240-US Installation and User Instructions. Please use below figure instead of the one mentioned in the table.

The diagram illustrates the rear panel of the PLE-2CS system with 27 numbered connection points:

- 1:** Speaker grille.
- 2:** Call Trigger terminal.
- 3:** PLE-2CS terminal block.
- 4:** Wall panel terminal block.
- 5:** D2 terminal block.
- 6:** D3 terminal block.
- 7:** D4 terminal block.
- 8:** D5 terminal block.
- 9:** D6 terminal block.
- 10:** D7 terminal block.
- 11:** Power input terminal block (115V ~, 230V ~).
- 12:** Telephone/Emergency terminal block.
- 13:** Chime terminal.
- 14:** Ducking terminal.
- 15:** Line Music Out terminal.
- 16:** Line Music Out terminal.
- 17:** Line Music Out terminal.
- 18:** Line Music Out terminal.
- 19:** Line Music Out terminal.
- 20:** Line Music Out terminal.
- 21:** Line Music Out terminal.
- 22:** Line Music Out terminal.
- 23:** Line Music Out terminal.
- 24:** 24V backup in/1A ma: terminal.
- 25:** 24V backup in/1A ma: terminal.
- 26:** 24V backup in/1A ma: terminal.
- 27:** 24V backup in/1A ma: terminal.